

MAIN OFFICE  
1455 New York Ave  
Huntington, Sta, NY, 11746  
(631) 427-5904  
FAX (631) 673-3301

PLANT  
366 Moffitt Blvd  
Islip, NY, 11751  
[www.Velvetop.com](http://www.Velvetop.com)

# Velvetop™

## P R O D U C T S

### **Specifications: Velvetop™ SLURRY Sealer**

#### **PRODUCT DESCRIPTION**

VELVETOP SLURRY Sealer is a high-performance sealer for asphalt pavement surfaces including parking lots, driveways, shopping malls, airports, low traffic roadways and more, it contains no Coal Tar.

Velvetop Slurry is ready to use. Polymers and surfactants are added to enhance color and durability to extend pavement life.

Aggregate is added for skid resistance and filling hairline cracks. The aggregate is a uniform sand of #60 mesh washed and fractured for better coating and resistance to “rolling out” of the finished coating after curing and use.

#### **FEATURES AND BENEFITS**

##### **Durable**

Longer lasting than other sealers.

##### **Color Stable**

Eliminates graying issues; will stay black and not fade.

##### **Fuel resistant**

Resists gasoline and oil penetration similar to coal tar sealer.

##### **Tougher**

Resists power steering mark.

##### **Water based low VOC**

Less than 100 grams per liter.

##### **Easy to apply**

Applies as smoothly as coal tar sealers

##### **Waterproof**

Seals out damaging effects of water and oil, extending the life of asphalt pavement.

##### **Consistent**

Manufactured in our precision colloid mill system, which takes the mystery out of mix design.

## **SPECIFICATIONS**

Velvetop SLURRY Sealer meets the following standards listed below:

<b>ASTM D5</b>	<b>ASTM D529</b>	<b>ASTM D4799</b>
<b>ASTM D140</b>	<b>ASTM D2939</b>	
<b>ASTM D466</b>	<b>ASTM D36</b>	

The following specifications have been used in the industry to set standards for coal tar- based products

### **Velvetop Slurry Sealer does not contain coal tar;**

Therefore, the industry specifications are not applicable. However, Velvetop does meet industry performance standards as follows:

**ASTM D5727**

**ASTM D 490**

**ASTM 3423**

**FAA P- 625; P- 627; and P- 630**

VelveTop™ shall be homogenous and show no separation or coagulation of components that cannot be overcome by moderate stirring. It shall be capable of application and complete coverage, by squeegee, brush, or by approved mechanical methods, to the surface of bituminous pavements at a total combined spreading rate of 1.5 to 2.5 gallons per 100 square feet in two coats.

## **CAUTION**

Pavement sealer is slippery prior to drying... exercise caution during application.

Do not apply VelveTop™ sealer when good weather is in doubt, or when the temperature is expected to drop lower than 50 before sealer is dry.

## **SAFETY WARNING**

Keep container tightly sealed when not in use and out of reach of children. Clean all tools with water immediately after used.

## **SHIPPING SIZE & WEIGHT**

5 Gal. Pail 52 lbs.

55 Gal. Drum 572 lbs.

Bulk Tanker 10.2 lbs per gal.

## **WARRANTY**

The buyer assumes all risks pertaining to the handling, storage and use of this product, whether or not it is used in accordance with directions and specifications. VelveTop™ makes no warranty to merchantability, fitness for particular uses, nor any warranty, expressed or implied.

**KEEP FROM FREEZING**