

Franklin Paint™

259 COTTAGE ST FRANKLIN, MA 02038
www.franklinpaint.com

Product Data: **SYNTHETIC FIELD MARKING PAINT**

DESCRIPTION: Temporary to permanent Synthetic Turf Paint, specifically formulated for use on synthetic athletic playing fields for sports such as football, soccer, field hockey, lacrosse, etc. supplied ready to use, no dilution required.

APPLICATION: Air and surface temperature should be above 50° F with a relative humidity of 85% max. Spraying is the preferred method of application to achieve clean sharp lines. Most conventional line marking machines will do the job. As with any paint to be sprayed straining is highly recommended (latex skins do not re-dissolve when mixed).

THINNING & CLEANING: If thinning of paint is desired, never exceed 1 quart of water to 5 gallons of paint, regardless of whether or not paint is thinned, stir to a smooth uniform consistency. For clean up water is usually sufficient on a daily basis. For a thorough cleaning, soap and warm water is recommended

SHELF LIFE: 12 months minimum based on unopened container stored @ 77° F

STORAGE: Store in a cool dry area. **KEEP FROM FREEZING**

	2250 White	COLORS (ALL)
State	Liquid	Liquid
Viscosity KU	70-74	70-74
Weight/Gallon	9.6	9.6
Brightness	Very High	N/A
Whiteness	Very High	N/A
Hiding	Very High	Very High
% Solids by Wt.	29	16 min
% Solids by Vol.	16.5	13 min
% Pigments by Wt.	15.5	10 min
% Titanium Dioxide*	100	N/A
Coverage/gal (5 mils wet 4" line)	960'	960'

*Primary pigment for brightness, whiteness & hiding