

MAIN OFFICE
1455 New York Ave
Huntington, Sta, NY, 11746
(631) 427-5904
FAX (631) 673-3301

PLANT
366 Moffitt Blvd
Islip, NY, 11751
www.Velvetop.com

Velvetop™

PRODUCTS

Specifications: Velvetop™ Super Pavement Sealer

PRODUCT DESCRIPTION

VELVETOP Super Pavement Sealer is a high performance sealer for asphalt pavement surfaces including parking lots, driveways, shopping malls, airports, low traffic roadways and more. It contains no Coal Tar.

FEATURES AND BENEFITS

Durable

Longer lasting than other sealers.

Color Stable

Eliminates graying issues; will stay black and not fade.

Fuel resistant

Resists gasoline and oil penetration similar to coal tar sealer.

Tougher

Resists power steering mark.

Water based low VOC

Less than 100 grams per liter.

Easy to apply

Applies as smoothly as coal tar sealers

Waterproof

Seals out damaging effects of water and oil, extending the life of asphalt pavement.

Consistent

Manufactured in our precision colloid mill system, which takes the mystery out of mix design.

SPECIFICATIONS

Velvetop Super Pavement Sealer meets the following standards listed below:

ASTM D5	ASTM D529	ASTM D4799
ASTM D140	ASTM D2939	
ASTM D466	ASTM D36	

The following specifications have been used in the industry to set standards for coal tar- based products

Velvetop Super Pavement Sealer does not contain coal tar;

Therefore , the industry specifications are not applicable. However, Velvetop does meet industry performance standards as follows :

ASTM D5727

ASTM D 490

ASTM 3423

FAA P- 625; P- 627; and P- 630

VelveTop™ shall be homogenous and show no separation or coagulation of components that cannot be overcome by moderate stirring. It shall be capable of application and complete coverage, by squeegee, brush, or by approved mechanical methods, to the surface of bituminous pavements at a total combined spreading rate of 1.5 to 2.5 gallons per 100 square feet in two coats.

CAUTION

Pavement sealer is slippery prior to drying... exercise caution during application.

Do not apply VelveTop™ sealer when good weather is in doubt, or when the temperature is expected to drop lower than 50 before sealer is dry.

SAFETY WARNING

Keep container tightly sealed when not in use and out of reach of children. Clean all tools with water immediately after used.

SHIPPING SIZE & WEIGHT

5 Gal. Pail 52 lbs.

55 Gal. Drum 572 lbs.

Bulk Tanker 10.2 lbs per gal.

WARRANTY

The buyer assumes all risks pertaining to the handling, storage and use of this product, whether or not it is used in accordance with directions and specifications. VelveTop™ makes no warranty to merchantability, fitness for particular uses, nor any warranty, expressed or implied.

KEEP FROM FREEZING